

Dry Bath (Incubator) ST-DBK30 - Economic

- Precise microprocessor control.
- Temperature and time can be set.
- Aluminium blocks ensure good temperature transfer.
- Blocks are circular.



Specification of Dry Bath (Incubator) ST-DBK30 - Economic

Model	ST-DBK30
Temperature Control Range	Ambient +5 ~ 100°C
Timer	1 min ~ 99 hr 59 min
Temperature Control Accuracy	± 0.5°C
Display Accuracy	0.1°C
Heating Time	≤ 20 min (20 ~ 100°C)
Standard Blocks	See below
Heating Parts	Heater
Display	LED
Dimension (L x W x H) mm	225 x 160 x 197
Net Weight	3kg
Power	150W
Power Supply	AC 220V 50/60Hz

Dry Block



Dry Block

Model	Type	Capacity	Dimension (mm)
ST-DB-A30	Centrifuge Tubes	96 x 0.2ml	Ø 108 x 32
ST-DB-B30	Centrifuge Tubes	29 x 0.5ml and 32 x 1.5ml	Ø 108 x 32
ST-DB-C30	Centrifuge Tubes	61 x 0.5ml	Ø 108 x 32
ST-DB-D30	Centrifuge Tubes	41 x 1.5ml	Ø 108 x 32
ST-DB-E30	Centrifuge Tubes	41 x 2.0ml	Ø 108 x 32
ST-DB-F30	Ø 6mm	61	Ø 108 x 32
ST-DB-H30	Ø 12mm	41	Ø 108 x 50
ST-DB-I30	Ø 13mm	36	Ø 108 x 50
ST-DB-J30	Ø 15mm	21	Ø 108 x 50
ST-DB-K30	Ø 16mm	21	Ø 108 x 50
ST-DB-L30	Ø 18mm	17	Ø 108 x 50
ST-DB-M30	Ø 20mm	14	Ø 108 x 50
ST-DB-N30	Ø 25mm	9	Ø 108 x 50