

Water Bath

- Digital temperature display.
- Alarm if temperature exceeds 2°C from set point.
- Epoxy powder coated external casing.
- Timer 1-999, 1-9999 minutes.
- PT100 thermocouple sensor.



Specification of Water Bath

Model	ST-420	ST-600	ST-DK600A
Capacity	15L	27L	32L
External Dimension (W x D x H) mm	550 x 280 x 300	730 x 340 x 310	750 x 400 x 300
Internal Dimension (W x D x H) mm	420 x 240 x 150	600 x 300 x 150	600 x 300 x 190
Temperature Range	Ambient +5-99°C		
Temperature Precision	0.1°C		
Temperature Uniformity	± 1°C		
Alarm	± 2°C		
Timer	1-999 minutes		
Power (W)	500W	1000W	1050W
Power Supply	AC 220V 50/60Hz		

Water & Oil Bath

- Digital temperature display.
- Alarm if temperature exceeds ± 2°C from set point.
- Embedded heating elements in stainless steel inner tank.
- Cold rolled metal for external casing with plated surface with slanted lid.
- Timer 1-999 minutes.



Specification of Water & Oil Bath

Model	ST-WB22	ST-WB24	ST-WB26	ST-WB28	ST-OB20
Capacity	10L	18L	25L	35L	15L
No. of Wells	2	4	6	8	-
Internal Dimension (mm)	360 x 200 x 150	360 x 340 x 150	500 x 340 x 150	700 x 340 x 150	700 x 340 x 150
Temperature Range	Ambient +5-99°C				Ambient +20-200°C
Temperature Precision	0.1°C				
Temperature Uniformity	± 1°C				
Alarm	± 2°C				
Timer	1-999 minutes				1-9999 minutes
Power	500W	1000W	1500W	2000W	1000W
Power Supply	AC 220V 50/60Hz				