

### Benchtop Shaker ST-344



#### Specification of ST-344

Model	ST-344
Display	LED
Oscillation Mode	Tilting
Speed Range	20~80 r.p.m.
Speed Accuracy	± 1 r.p.m.
Tilting Range	5°, 8°, 10°, 12° adjustable
Maximum Capacity	4 plates
Maximum Load	4kg
Platform Size (mm)	270 x 250
Weight	8kg
Overall Dimension (mm)	300 x 270 x 150
External Material	ABS special engineering plastic
Power	18W
Power Supply	AC 220V 50/60Hz

### Benchtop Shaker ST-304



#### Specification of ST-304

Model	ST-304
Display	LED
Oscillation Mode	Orbital
Speed Range	50~300 r.p.m.
Speed Accuracy	± 1 r.p.m.
Oscillation Amplitude	Ø 26mm
Maximum Capacity	9 x 250ml
Maximum Load	12kg
Platform Size (mm)	290 x 310
Weight	15kg
Overall Dimension (mm)	300 x 310 x 230
External Material	ABS special engineering plastic
Power	40W
Power Supply	AC 220V 50/60Hz

### Benchtop Shaker ST-310



#### Specification of ST-310

Model	ST-310
Display	LED
Oscillation Mode	Orbital / Reciprocal
Speed Range	50~300 r.p.m.
Speed Accuracy	± 1 r.p.m.
Oscillation Amplitude	Ø 26mm
Maximum Capacity	12 x 1L
Maximum Load	30kg
Platform Size (mm)	550 x 450
Weight	50kg
Overall Dimension (mm)	550 x 650 x 320
External Material	ABS special engineering plastic
Power	65W
Power Supply	AC 220V 50/60Hz
Timer	0-500 Hours

### Platelet Incubator Shaker

- Single-chamber, single compressor and heater and shaker.
- Microprocessor electronic temperature regulator.
- Automatic temperature control. Temperature range: 10°C to 37°C, preset at 22°C.
- Digital temperature display.



#### Specification of Platelet Shaker

Model	ST-RTB2100-10
Shaker Speed	6~60 r.p.m.
Power	230V 50Hz, 200W
Compliance	IEC 1010-1, BSEN61010-1:1993 CE Marked
Speed Accuracy	± 1 r.p.m.
Volume	85L
Internal Dimension (W x D x H)	410 x 380 x 550
External Dimension (W x D x H)	485 x 480 x 800
Shipping Weight	75kg
Warranty Period	24 months
Complete with	10 shelves, 6 bags each or 3 bags each plasma pheresis bags