



Priorclave details - model no PS/MID/C60.

Compact 60 Top Loading Priorclave autoclave. (Includes cooling & automatic Timed Freesteaming)

The **Priorclave Compact 60** autoclave is top loading with a 60L capacity and is mounted on lockable castors. This and its compact size makes it ideal for confined areas or laboratories with an occasional requirement for an autoclave. It is supplied complete with a stainless steel load support plate and two baskets. A stainless steel waste container is also available.



Compact Priorclaves.

These autoclaves allow a level of setting and operating flexibility usually only available in larger units for the low volume user and are ideally suited for use in a wide range of sterilising applications such as media preparation, laboratory waste, liquids and diluents, glassware, instruments and apparatus.

They are extensively used within many industries including food, drink, dairy, pharmaceutical, agricultural, education, healthcare, research establishments and industry.

Features include:

- Operation up to 140C – 2.5 Bar.
- Quickseal 2 single action closure
- Operation from standard 13 Amp socket (UK)
- Complete with thermocouple entry and test ports
- Forced air cooling as standard helping to reduce cycle times
- Automatic timed freesteaming as standard for improved air removal and sterilising performance
- Delayed start and media warming function as standard for ready to pour media at the start of the day

A large selection of options and accessories is available to help to get the most from your Priorclave autoclave.

All models are fitted with the **TACTROL** microprocessor control system. After setting your required operating parameters press the start button for a fully automatic cycle. The control panel shows cycle status with digital readouts of temperature and time that can be viewed simultaneously. Temperature and time settings are fully adjustable within the operating range of the autoclave.

Safety

Pressure vessels are fully **CE** marked and insurance approved to the European PED 97/23/EC. The autoclaves fully conform to BS2646-1993, BS5500 Cat.3, and EMC directives, amongst others. The autoclave door is fully interlocked for safety with a special safety gate mechanism, which cracks the gasket seal allowing any residual pressure to safely escape. A thermal cooling lock, preventing the door from being opened until the contents have cooled to a safe temperature is also fitted along with a pressure interlock. A low water level sensor, to guard against boil-dry conditions and a safety blow down valve afford further protection.

Epoxy coated panels and frame members are treated with the unique **Biocote**[®] anti-bacterial agent, which is effective against all bacteria and fungi including MRSA.

Installation Requirements

Electrical: Single phase 230V, 50Hz, 13-amp power supply (3kW).

Drainage: The single vent outlet pipe can be directed to a nearby drain. For make safe processing the discharge should be directed to a sealed discharge system; the system should lead by direct connection to a building drain or catchment tank.

For more specific advice about your particular installation requirements please contact our Technical Department or download our data sheet outlining the installation requirements for Priorclaves or any other type of Laboratory autoclave at: <http://www.priorclave.co.uk/downloads/installation.PDF>

Compact Priorclave autoclaves have a 12 months parts and labour warranty (parts only outside the UK) and a 10 year, 10,000 cycle pressure vessel warranty.

Technical Specifications.

Max. Capacity: 60L

Internal Diameter: 350mm

Load height: 850mm

Dimensions (mm)	Width	Depth	Height	Packed Dimensions (mm)	Width	Depth	Height
Internal	-	625	-	UK Delivery	720	900	950
External	475	585	910	Delivery by Sea	-	-	-
Installed	475	910	635	Delivery by Air	-	-	-

Weights (Kg)	
Gross	90
Packed (Sea)	150
Packed (Air)	-

NB: Weights and dimensions shown are for the Autoclave only, unloaded and without water (if applicable). These figures do not include any options and accessories listed below which may alter external dimensions and weights. For full details please contact Priorclave or your local agent.
